

# **LUBEALLOY**

## **SPECIALISED LUBRICANTS**

### **LA 280 Open Slide-way & Chain Lubricant**

#### **Description**

LA 280 is a chain and way lubricant specially engineered for a wide range of applications. It is a combination of superb, select base oils and highly-fortified extreme pressure supplements. It provides exceptional protection and substantially increases the operating life of equipment.

#### **High Viscosity**

- Features high adhesiveness agents that will provide total protection to the metal surface
- Eliminates start-up drag on opposing metal surfaces

#### **Resistant to Oxidation**

- Helps keep applied surfaces and chain linkage free from blockage that would hinder smooth operation
- Eliminates scuff-wear to teeth on cogs and gears from carbonaceous deposits

#### **Extended Lubricant Life**

- Superior degree of tenacity
- Forms a tough, anti-compressive, anti-drip film that prevents seeping out and moving away from the contact areas
- Equipment life is greatly extended by the lubricant staying in place

#### **Load Carrying Capability**

- Fortified with extreme pressure constituents
- Resistance to shock, load and impact
- Highly recommended for even severe operating conditions
- Prevents stick slip on machine slide-ways and chain powered equipment

#### **Rusting and Corrosion Protection**

- Maintains lubrication even under oil/water conditions
- Fortified with rust and corrosion inhibitors to protect the metal surface of all metals experienced within industry

#### **Machine Energy Efficiency**

- Designed to penetrate "oil line feeders"
- Provides the necessary lubrication for chains and side-ways
- Maintains complete "slip" of all opposing surfaces, therefore increasing productivity and energy efficiency of the power output equipment