

LUBEALLOY

SPECIALISED LUBRICANTS

LA 354 Gasoline & Light Diesel Engine Oil

Description

LA 354 Gasoline and Light Diesel Engine Multi-grade lubricant is a high performance, high shear stable engine oil for up-market naturally aspirated and turbocharged gasoline and diesel four stroke engine combustion vehicles. LA 354 provides vastly improved protection resistance against engine wear, high temperature oxidation deposits and sludge formation as well as protection against low temperature “black sludge” development from the excellent detergency-dispersion inclusion to exceed ACEA A3/B4-10 requirements.

Higher Viscosity

- Extended oil drain periods
- Low temperature cold starts and engine protection

Shear and Thermal Stability

- High viscosity shear and thermal stable PARASYN base oil
- Provides anti-wear protection to rings, cylinders, bearings, timing gear, valve train and all moving engine surfaces

Alkali Reserves

- Protects the metals of engines by high levels of alkali reserve supplements
- Contains rust and corrosion inhibitors protect the precious metals prone to condensation tendencies in cooling engines after engine shut down

Extended Catalytic Converter Life

- Catalytic converter life is extended due to the balance of anti-wear additives
- Minimised catalyst poisoning
- Impeding catalyst glazing

Superior Friction Reduction

- Contains “Energy Saving”
- Increased engine power efficiency resulting in less litres of fuel per 100 kilometres

Viscosity @ 40°C, cSt	96.068
Viscosity @ 100°C, cSt	14.614
Specific Gravity	0.860
Viscosity Index	159
NOACK Volatility	9.60
HTHS @ 150°C (cP)	4.12
Pour Point, °C	-33
Flash Point, COC°C	265