



## LA 75 & LA 76 Transmission Oil

### Description

LA 75-SAE 70W/80 and LA 76-SAE 75W/85 Transmission Oils are formulated with PARASYN™ base oil and select additive technology that protect and enhance transmissions which are designed with yellow metals (brass, bronze, copper) and other 'soft' metals incorporated in construction of synchronisers, bushings, thrust washers and other components commonly particularly found in time-honoured manual transmissions and transaxles.

### Oil Film Strength and Durability

- Protection for gear teeth under torturous speed and gear shift operations of racing gear change

- Prompt dissipation of heat to eliminate oil shearing and rupturing under strenuous loads
- Durable formulation resists viscosity loss due to mechanical shear to maintain a strong protective oil film
- Heavily fortified with HYPER-ZINC, 'primary alkyl' sulphur and phosphorus anti-wear additives

### Operating Temperatures

- Quick flow properties in below zero (0°C) degree temperatures

### Corrosion Inhibitors

- Corrosion and oxidation inhibitors protect the *soft yellow metals*

TEST SPECIFICATIONS	LA 75	LA76
Viscosity Grade SAE	70W/80	75W/85
Viscosity, 40°C, cSt	25.90	92.24
100°C, cSt	5.61	12.70
Viscosity Index	167	134