



SPECIALISED LUBRICANTS

LA 191 Semi-Fluid Grease NLGI -\'0' & \'00' JAN 2024 - PRODUCT CODE 60191&60192

COMPANY DETAILS

Company Name LubeAlloy Specialised Lubricants Pty Ltd **Address** 19A Stephens Road, Queanbeyan, NSW, 2620

Telephone Number 02 6284 4966 02 6284 4355 **Fax Number Emergency Phone Number** 02 6284 4966

Section 1: PRODUCT IDENTIFICATION

Product Name LA191-0 & 00

Product Description Synthetic Base Grease with Complex Additives

UN Proper Shipping Name N/A

Recommended Use Plain and Anti-Friction Bearings, Slides

Section 2: HAZARDS IDENTIFICATION

Precautions Keep out of reach of children.

Avoid release to the environment.

NOHSC Classification Not classified as hazardous according to criteria of National Occupational Health and Safety

Commission (NOHSC).

ADG Classification Not classified as a Dangerous Good according to the Australian Code for the Transport of

Dangerous Goods by Road and Rail.

Note: Combustible materials may be classified as Class 9: miscellaneous dangerous goods if

transported with flammable materials. See ADG code for further information.

SUSDP Classification Not scheduled

Section 3: FIRST AID MEASURES

Swallowed DO NOT INDUCE VOMITING. Immediately wash out mouth with water, and then give plenty of water to

drink. Seek medical attention.

Rinse eyes immediately with water for at least 15 minutes. In case of irritation, seek medical advice. Eye

Skin Remove all contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap.

Ensure contaminated clothing is washed before re-use or discard. If irritation develops and persists,

seek medical attention.

Inhaled Remove the patient to fresh air. Ensure airways are clear and have qualified person give oxygen

through a facemask if breathing is difficult. If irritation develops, seek medical attention.

No special facilities required. **First Aid Facilities**

Advice to Doctor Treat symptomatically.

Section 4: FIRE FIGHTING MEASURES

Fire/Explosion Hazard Classified as C2 (Combustible liquid)

Extinguishing Media Use water as a fog or spray to cool fire exposed containers

Do not use direct stream of water; product will float, possibly re-igniting.

Fire Fighting Precautions Self-Contained Breathing Apparatus and full protective clothing should be worn Flash Point (COC)

None

Hazchem Code Not Applicable **Hazards from Combustion Products** Oxides of carbon.

Page 1 - 60191&2v24





Section 5: COMPOSITION/INFORMATION ON INGREDIENTS

Proportion Name **CAS NUMBER**

70 - 90% **Base Greases Propietary Lubricant Additive Complex** 10 - 30% Confidential

Section 6: ACCIDENTAL RELEASE MEASURES

Spills Procedure SMALL - 20 LITRES OR LESS

Soak up with inert oil absorbent. Arrange for disposal through an approved facility.

LARGE - GREATER THAN 20 LITRES

Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective clothing and equipment to minimize exposure. If possible, contain the spill. Place inert absorbent material such as vermiculite, sand or dirt onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labeled container. If large quantities of this material enter the waterways contact the Environment Protection Authority, local government statutory authority, or your local Waste Management Authority.

Section 7: HANDLING AND STORAGE

Handling Repeated or prolonged contact with this material should be avoided in order to lessen

the possibility of skin disorders. It is essential that all who come into contact, maintain high standards of personal hygiene ie, washing hands prior to eating, drinking or going to the toilet. Build-up of mist in the working atmosphere must be prevented. Misuse of empty containers can be hazardous. Do not cut, weld, heat or drill containers. Residue may ignite with explosive violence if heated sufficiently. Do not pressurize or expose to open flame or heat. Keep container closed and bung in place. Classified as a combustible substance for storage and handling purposes. Store in a cool, dry, well-ventilated area, out of direct sunlight. Avoid sparks, flames and other ignition sources. Store away from incompatible materials such as materials that

Storage Precautions support combustion (oxidizing materials). Reference should be made to Australian

Standard AS 1940 – The Storage and Handling of flammable and combustible liquids.

Section 8: STABILITY AND REACTIVITY

Stability Stable under conditions of storage and handling.

Conditions to Avoid None allocated. **Incompatible Materials** Strong oxidizing agents.

Hazardous Decomposition Products Oxides of carbon

Hazardous Reactions No hazardous polymerization will occur.

Section 9: ECOLOGICAL INFORMATION

Eco-toxicity No ecotoxicological classifications.

Persistence and Degradability No data available. No data available. Mobility





Section 10: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC). However, Exposure standards and ACGIH limits for the constituents are listed below.

SUBSTANCE	TWA		STEL	
	ppm	mg/m³	ppm	mg/m³
Oil mist, mineral	-	5	-	10

Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short-term exposure limit (STEL)

No biological limit allocated.

Biological Limit Values Engineering Control

The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures or otherwise, to maintain ambient

concentration below the recommended threshold exposure limits.

Respirator Type Avoid breathing vapours or mists. Select and use respirators in accordance with AS/NZ

1715/1716. When vapours are generated, the use of the following is recommended: Half face piece respirator with dust/mist filters. The appropriate filter capacity and respirator type will depend on exposure levels encountered.

Eye Protection Glove Type Clothing Chemical safety goggles are recommended. If handled hot, a full face shield should be worn.

Use of impervious rubber gloves is recommended.

Clothing should be suitable to avoid product contacting the skin on a prolonged or repeated

oasıs.

Section 11: PHYSICAL AND CHEMICAL PROPERTIES

Appearance Smooth Black Grease Odour Petroleum Odour

Melting Point >260°C
Boiling Point N/A
Vapour Pressure N/A
Vapour Density N/A
pH Specific Gravity 0.898

Flashpoint (COC)

Flammable Limit LEL

Flammable Limit UEL

-

Solubility in Water <0.1 g/l

Viscosity @ 1000°C -

Section 12: TOXICOLOGICAL INFORMATION

Toxicology No adverse health effects expected if the product is handled in accordance with this MSDS.

Acute – Swallowed Small amounts of liquid aspirated into the respiratory system ingestion or from vomiting may cause

bronchopneumonia or pulmonary edema.

Acute – Eye Will cause eye discomfort, but will not injure eye tissue.

Acute – Skin Prolonged or frequent contact may cause skin irritation or cracking to sensitive skins.

Acute – Inhaled Vapour concentrations above recommended exposure levels may be irritating to the eyes and the

respiratory tract, may cause headaches and dizziness, or could be anesthetic and may have other

central nervous system effects.

Chronic Prolonged or repeated contact with this material may result in skin irritation leading to dermatitis.

Page 3 - 60191&2v24





SPECIALISED LUBRICANTS

Section 13: DISPOSAL CONSIDERATIONS

Disposal MethodDispose of waste according to Federal, EPA, state and local regulations. Assure conformity with

all applicable regulations government body.

Special Disposal Precautions None Allocated.

Section 14: TRANSPORT INFORMATION

UN Number None allocated UN Proper Shipping Name None allocated

DG ClassNot classified as a Dangerous Good according to the Australian Code for the Transport of

Dangerous Goods by Road and Rail.

Not classified as a Dangerous Goods according to the IATA for transport by air.

Note: Combustible materials may be classified as Class 9; miscellaneous dangerous goods if

transported with flammable materials.

Packaging GroupNone allocatedHazchem CodeNone allocatedSpecial Transport PrecautionsNone allocated

Section 15: REGULATORY INFORMATION

AICS All ingredients present on AICS

Section 16: OTHER INFORMATION

Acronyms ABN Australian Business Number

ACGIH American Conference of Government Industrial Hygienists

ADG Australian Dangerous Goods **AEST** Australian Eastern Standard Time

AICS Australian Inventory of Chemical Substances
CAS Chemical Abstracts Service Registry Number

COC Cleveland Open Cup
DG Class Dangerous Goods Class
EPA Environment Protection Agency

Hazchem Code of numbers and letters which gives information to emergency services

IATA International Air Transport Association

IP Institute of Petroleum

NOHSC National Occupational Health and Safety Commission
OECD Organisation of Economic Co-operation and Development

PMCC Pensky-Martens Closed Cup

SUSDP Standard for the Uniform Scheduling of Drugs and Poisons

UN Number United Nations Number

Section 17: CONTACT POINT

ContactTechnical ManagerTelephone(+61) 02 6284 4966

IMPORTANT DISCLAIMER All reasonable care has been taken to ensure that the information and advice contained herein

is accurate at the time of publication. However, LubeAlloy Specialised Lubricants or LubeAlloy Manufacturing Australia accepts no tortuous or contractual liability for any loss or damage suffered as a consequence of reliance on the information and advice contained herein.